




## MTN/1120IC Series

General purpose industrial accelerometer

### Applications

- Paper machinery
- General industry
- Pumps, fans, etc.
- Air handling units
- Machine tools



### Technical Specification

Standard Sensitivity	100 mV/g $\pm 10\%$ nominal at 80 Hz
Frequency Response	2 Hz to 10 kHz $\pm 5\%$ (-3 dB at 0.8 Hz)
Mounted Base Resonance	20 kHz (nominal)
Isolation	Base isolated
Dynamic Range	$\pm 80g$
Transverse Sensitivity	Less than 5%
Electrical Noise	0.1 mg max
Current Range	0.5 mA to 8 mA
Temperature Range	-55 to 140 °C
Temperature Sensitivity	0.08 %/°C
Bias Voltage	12 Volts (nominal)
DC Supply	+18 to 30 Volts
Case Material	Stainless steel
Cable	Integral stainless steel, overbraided PTFE
Standard Cable Length	5 metres
Maximum Cable Length	1000 metres
Mounting Torque	8 Nm
Weight	45 gms (nominal)
Sealing	IP67
Options	Connector, side entry, cable length, various mounts, other sensitivities (see table).

ORDER CODE PART No	MOUNTING	xx = OPTIONAL SENSITIVITY RANGE AVAILABLE (+/- 10%)
MTN/1120ICF1/4-xx	1/4" UNF FEMALE	
MTN/1120ICQ-xx	QUICK FIT FEMALE	0-10 mV/g
MTN/1120ICF-xx	10-32 UNF FEMALE	0-30 mV/g
MTN/1120ICF6-xx	M6 FEMALE	0-50 mV/g
FOR OTHER MOUNTINGS SEE OVER PAGE		0-500 mV/g


# Mounting Adapters and Studs

## Studs and Grub Screws



Male Studs		
Product Code	From	To
MS036	1/4" - 28 UNF	M6
MS039	1/4" - 28 UNF	10 - 32 UNF
MS067	1/4" - 28 UNF	M8
MS068	1/4" - 28 UNF	1/4" - 28 UNF
MS124	1/4" - 28 UNF	M10
MS132	1/4" - 28 UNF	M12


## Quick Fit Adapters



1120 Quick Fit (Q/F)		
Product Code	From	To
MS010	1120 Q/F Male	Glue base
MS055	1120 Q/F Male	M8 Male
MS072	1120 Q/F Male	M6 Male
MS102	1120 Q/F Female	10 - 32 UNF Male
MS117	1120 Q/F Male	1/4" - 28 UNF Male

1120 Studs		
Product Code	From	To
MS021	1/4" - 28 UNF	M8

## Other Adapters



Mounting Adapters		
Product Code	From	To
MS011	1/4" - 28 UNF Male	Q/F Female
MS013	1/4" - 28 UNF Male	Glue base
MS033	1/4" - 28 UNF Male	Q/F Female
MS061	1/4" - 28 UNF Male	10 - 32 UNF Male
MS079	1/4" - 28 UNF Male	Q/F Female

Isolation		
Product Code	From	To
MS034	1/4" - 28 UNF Male	1/4" - 28 UNF Female
MS027	M6 Male	M6 Female

## System Connection

